

Warszawa 07.03.2024

TDS FILE

Frontlit Premium PVC free 300 g/m², SAP Index BFRN300M*

PRODUCT DESCRIPTION:

- PA – coated, 1000x1000, 20x20 base fabric
- PVC FREE, PHTHALATE FREE, LIGHT WEIGHT, GOOD OPACITY

APPLICATION:

- can be used as outdoor or indoor banners

PRINTING METHOD:

UV / LATEX / ECO SOL INKS

PROCESSING: welding, stapling and mounting with a double side adhesive tape

PROPERTIES	TEST METHOD	METRIC / IMPERIAL
Total weight	DIN EN ISO 2286-2, ASTM D751	320g/sqm 9.4 oz/sq.yd
Base fabric	DIN 60001, ASTM D7641	100% polyester
Yarn Dtex	DIN EN ISO 2060, ASTM D 1907	1100X1100 dtex / 1100x1100 denier
Shielding rate	ANSI PH2.19, ISO 5/2	85%
Tensile Strenght	DIN EN ISO 1421	2290x2180 N/5cm / 263x251 lbs/inch
Tear Strenght	DIN 53363	730x690 N 164x155 lbs
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 500cm, 197"
Standard Lenght	DIN EN ISO 3759, ASTM D751-2006	50m, 55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit of warranty