

Warszawa 11.07.2024

TDS FloorLam Eco R9 100um matt

SAP Index SALF100M*

Description: Soft Monomeric PVC film

Color: Transparent

Surface: Matte

Release Liner: 140±10gsm PE-Coated silicon paper.

Adhesive: Solvent polyacrylate, Permanent, Transparent.

Technical data:

CHARACTERISTIC	TEST METHOD	AVERAGE VALUE
Thickness without adhesive and protective paper		100+/- 10 micron monomeric PVC Film
Adhesive type		Solvent polyacrylate, permanent transparent
Dimensional stability	FINAT TM14	Adhered to steel, No shrinkage in cross direction, in length 0.50mm max
Slip resistance	(oil-wet ramp test)	R9 *critical angle of inclination 9.6°
Temperature resistance		Adhered to aluminum , after -20°C to +60°C, no variation
Sea water resistance	DIN 50021	Adhered to aluminum, after 48h /+23°C, no variation
Adhesive power	FINAT TM1	After 24h stainless steel 16±2N/25mm
Tensile strength Along Across	ASTM D882-02; 200mm/Min	Min. 22Mpa Min. 18Mpa
Elongation break Along Across	ASTM D882-02; 200mm/Min	Min. 200% Min. 150%
Shelf life		UP TO 1 YEAR
Application temperature		Min. +10°C
Service life under vertical outdoor exposure		Up to 1 year

Attention: After printing the ink must be thoroughly dry in order to avoid any effect on the later combination with the laminate. Surfaces to which the material will be applied must be thoroughly cleaned from dust, grease or any contamination which could affect the adhesion of the material. The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications customers should independently determine the suitability of this material for their specific purpose, prior to use.

public - 2024-07-11T16:01:06 - a.koscielniak@europapier.pl



HEINZEL
GROUP

EUROPAPIER®

public - 2024-07-11T16:01:06 - a.koscielniak@europapier.pl



Europapier Polska Sp. z o.o., Aleje Jerozolimskie 142 A, 02-305 Warszawa T +48 22 - 356 92 00, F +48 22 - 356 92 90, E-mail: biuro@europapier.pl, www.europapier.pl, Sąd Rejonowy dla m.st. Warszawy w Warszawie, XII Wydział Gospodarczy Krajowego Rejestru Sądowego KRS: 0000112435, Wysokość kapitału zakładowego: 21.020.000,00 zł, REGON: 191095216, NIP: 593-10-92-550, Nr VAT UE PL 5931092550.

Niniejszy dokument ma poufny charakter i jest skierowany wyłącznie do adresata firmy Europapier Polska Sp. z o. o. Bez zgody firmy Europapier Polska Sp. z o. o. nie może być przekazywany do innych odbiorców.