

Warszawa 13.02.2025

TDS FILE PROTECTIVE PAPER 32g

SAP index PP32*

PRODUCT DESCRIPTION:

Protective paper for sublimation – protect your calender line from gassing inks

High quality kraft plain paper, 32 gr/m², used to protect the calender felt or press plate during the sublimation process.

Applications:

Indicated for protecting the substrate used in transfer applications. Prevents yellowing of white synthetics during the transfer process.

PROPERTIES	TEST METHOD	METRIC / IMPERIAL
Total weight	PN-ISO 536	32g/m ²
Tolerance of weight	N/A	+1.5 g/m ² - 1.5 g/m ²
Tensile breaking strength	PN-EN ISO-1924-2	MD min 2.83 std 3.45 [kN/m] CD min 1.19 std 1.41 [kN/m]
Tearing resistance	PN-EN 21974	MD min 160 std 200 [mN] CD min 220 std 260 [mN]
Burst resistance	PN-EN ISO-2758	Std 1.9 [kPa] Min 1.4 [kPa]
Water absorption Cobb60	PN-ISO-535	30 [g/m ²]
Moisture	EN 20287	6-9 [%]
Core diameter		76 mm / 3 inch
Width Available	DIN EN ISO 3759, ASTM D751	165 cm, 320cm
Standard Weight	DIN EN ISO 3759, ASTM D751	30, 60, 120 kg