

Warszawa 15.07.2024

TDS FILE myMEDIA 4410 Quality Flag FR

SAP code: MY4410*

PRODUCT DESCRIPTION:

- 100% polyester warp-knitted textured fabric with semi-matte surface
- Perfect as flag
- PVC & PHTHALATE free, OEKO-TEX STANDARD 100 certificate

PRINTING METHOD:

DIRECT and TRANSFER SUBLIMATION

APPLICATIONS: Flags, banners

PROPERTIES	TEST METHOD	METRIC / IMPERIAL
Total weight	DIN EN ISO 2286-2, ASTM D751	110g/sqm 3.2 oz/sq.yd
Base fabric	DIN 60001, ASTM D7641	100% polyester
Weave method	N/A	Warp-knitted
Shrinkage	N/A	≤2% (210°C, 30s)
Flame resistance	DIN 4102-1-B1, NFPA 701 Test1	DIN 4102-1-B1, NFPA 701 Test1
Recommend Fixation Temperature	N/A	190- 210°C, 1-2 min
Yellowing Temperature	SUPRKC REX-C400, 30s	≥ 210°C
Width Available	DIN EN ISO 3759, ASTM D751	Max 320cm, 126"
Standard Length	DIN EN ISO 3759, ASTM D751	100m, 110yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only use as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit of warranty