



Art Opaque 80 / A251 / WK80

FACE STOCK

Art Opaque

Description Art gloss coated woodfree paper with an opaque treatment on the reverse.

Applications High resolution standard gloss label used to block-out existing printed information (i.e. prices).

Printing techniques Suitable for printing on flexo (all types), letterpress (conventional and UV), conventional offset, offset UV, hot stamping, thermal transfer, laser.

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m ²	80	± 4%
Thickness	ISO 534	µm	61	± 6
Bekk smoothness	ISO 5627	s	≥1300	
Opacity	ISO 2471	%	99,7	-2

ADHESIVE

A251

Description General use acrylic permanent adhesive including smooth and slightly rough or curved surfaces.

Shelf life From the date of manufacture 2 years in 20°C and RH 50%

Property	Method	Units	Value	Tolerance
Adhesion (Peel 180° 20' / stainless steel)	FTM 1	N/25mm	15,4	≥ 12,3
Shear (1 kg, in ² /glass)	FTM 8	min	100	≥ 60
Tack (Quick Stick stainless steel)	FTM 9	N	10,3	≥ 7,8
Minimum labelling temperature		°C	5	
Minimum service temperature		°C	-20	
Maximum service temperature		°C	80	

LINER

WK80

Description One-side coated white liner with good lay-flat characteristics. Suitable for sheeting.
Available only in solid back

Color White

Property	Method	Units	Value	Tolerance
Substance	ISO 536	g/m ²	80	± 4%
Thickness	ISO 534	µm	81	± 4
Tensile strength MD/CD	ISO 1924-2	kN/m	4,6/2,3	2

- Values are subject to change without notice. Last updated 01/09/2016.
- The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.