## **JAC GRAPHICS JAC METALLI**

+80

## Average values **Print carrier**

JAC Metallic is a series of paper-laminated foils available in a variety of colour shades. They are used for the manufacture of high-quality labels and stickers, e.g. corporate emblems, nameplates on machines and kitchen appliances, quality seals etc., and for the labeling of up-market cosmetic products. JAC Metallic is suitable for all (excluding digital print) printing processes (special printing inks are required for letterpress and offset).

52060 - silver, matt 52160 - silver, gloss

flatness.

For technical guidance please visit our website under Downloads "Guidelines for use "- Printing .

	52060	52160	
Weight (g/m²)	81	83	
Thickness (µm)	66	66	
Shelf life of laminate <sup>1)</sup> (years)	2	2	

<sup>1)</sup> Stored in original packaging at a temperature defined by FINAT (20- 25°C; 40-50%RH)

## Average values **Adhesive DURO DURO D2010** D2010 A general purpose permanent, acrylic based adhesive. Adhesion (N/25 mm) 9 The adhesive is characterized by a high initial tack, (FTM 2 on st.steel/20 min. bond time) excellent adhesion and good low temperature Tack (N/25 mm) 16 performance on a wide variety of substrates. (FTM 9 on glass) Recommended minimum > 5 application temperature (°C) -20

Service temperature

For information regarding EHS regulation please visit our website under Downloads "Guidelines for Use" 5.12 Product Compliance Jac Screen

Silicone paper	Average values	
B 80 - siliconized kraft, wood-free, special-purpose		B 80
paper, moisture-stabilized through a special coating on one side.	Weight (g/m²)	82
It displays high dimensional stability and excellent	Thickness (um)	79

Warranty and liability Issued June 2015

All Avery Dennison and JAC® statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison and JAC® products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison and JAC® products are sold subject to Avery Dennison's general terms and conditions of sale, see http://terms.europe.averydennison.com

©2015 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison. This issue replaces all previous issues.



<sup>1)</sup> Not fully resistant until after adhesion reaches full strength – after at least 24 hrs