

Warszawa 26.02.2024

TDS FILE myMEDIA 4232 Harmony Fabric UV FR 220g

PRODUCT DESCRIPTION:

- 100% polyester warp knitted fabric with a tight structure
- Max 5m width makes the product more widely used
- Specially developed for UV Printing

PRINTING METHOD:

UV, LATEX, ECO SOL Inks

PROPERTIES	TEST METHOD	METRIC / IMPERIAL
Total weight	DIN EN ISO 2286-2, ASTM D751	220g/sqm 6.5 oz/sq.yd
Base fabric	DIN 60001, ASTM D7641	100% polyester
Weave method	N/A	Warp-knitted 2 bar
Shielding rate	ANSI PH2.19, ISO 5/2	60%
Flame resistance	DIN 4102-1-B1, NFPA 701 Test1	DIN 4102-1-B1, NFPA 701 Test1
Yellowing Temperature	SUPRKC REX-C400,30s	≥210°C
Flame Resistance	DIN 4102-1-B1, NFPA701 Test1,	DIN 4102-1-B1, NFPA701 Test1,
Width Available	DIN EN ISO 3759, ASTM D751	Max 5,000cm, 197"
Standard Length	DIN EN ISO 3759, ASTM D751	50/100m, 55/110yds
<p><i>NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only use as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit of warranty</i></p>		