

Warszawa 14.02.2024

TDS FILE

SUN BEDS WATERPROOF FABRIC 190g FRB1

PRODUCT DESCRIPTION:

- 100% polyester fabric with 500D x 500D woven base
- Good tensile, tear strength & water resistance feature
- Can be used as short-time promotion tent, parasol, etc
- PVC FREE, PHTHALATE FREE, WATER PROOF

APPLICATION:

. Indoor and Outdoor

PRINTING METHOD:

DYE SUB TRANSFER PAPER, UV, ECO SOLV, LATEX

PROPERTIES	TEST METHOD	METRIC / IMPERIAL
Total weight	DIN EN ISO 2286-2, ASTM D751	190g/sqm 4.4oz/sq.yd
Base fabric	DIN 60001, ASTM D7641	100% polyester
Water Proofness	Approx. 600 mm.H2O	N/A
Yarn Dtex	DIN EN ISO 2060, ASTM D1907	550x550 dtex 500x500 denier
Weave method	N/A	Woven
Shrinkage	210°C,30s	≤3%
Tensile Strength	DIN EN ISO 1421	2024X1110 N/5cm, 231x127 lbs/inch
Tear Strength	DIN53363	251x189 N, 56X43lbs
Flame Resistance	SGS	B1
Recommend fixation temperature	N/A	190°C, 30s
Width / Length Available	DIN EN ISO 3759, ASTM D751	Max 320cm, 126" / 50m, 55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only use as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit of warranty

